

PRODUCTSPECIFICATIONS





STANDARD FEATURES

- Engine: Deutz TCD 7.8
- Boom suspension system
- Differential Locking Axle
- Automatic Transmission Kick Down
- Bucket Self-Leveling and Return to Dig

- SANYLive Telematics
- Single joystick control
- Third Function Hydraulics
- Reversible fan
- Rear view camera


- Net Power
 117.8 kW / 158 hp
- Bucket Capacity
 2.29 m³ / 3.2 yd³
- Operating Weight14,616 kg / 32,222 lb
- Full Turn Tipping Load 7714 kg / 17,007 lb






PRODUCT **SPECIFICATIONS**

MODEL: SW305K Wheel Loader





OVERALL DIMENSIONS

		METRIC	STANDARD
1	Height to Axle Centerline	695 mm	2' 3"
2	Height to Top of Cab	3405 mm	11, 2"
3	Center Line of Rear Axle to Edge of Counterweight	1911 mm	6' 3"
4	Wheelbase	3000 mm	9' 10"
5	Center Line of Front Axle to Center Pivot	1500 mm	59"
6	Shipping Length without Attachment	6562 mm	18' 7"
7	Shipping Length with Bucket	7511 mm	24' 8"
8	Max. Dump Height	5214 mm	17' 1"
9	Hinge Pin Height at Max. Lift	3834 mm	12' 7"
10	Dump Clearance at Max. Lift	2689 mm	8' 10"
11	Dig Depth, Level Bucket	117 mm	4.6"
12	Reach at Max. Lift and 45° Discharge	993 mm	39"
13	Roll Back at Max. Lift		1°
14	Dump Angle at Max. Lift and Dump	4:	5°
15	Roll Back at Carry Height	4:	9°
16	Roll Back at Ground	4:	5°
17	Tail Angle to the Rear Wheel	28	8°
18	Clearance Circle to Outside of Tires	5382 mm	17' 8"
19	Clearance Circle to Counterweight	5338 mm	17' 6"
20	Max. Circle	5994 mm	19' 8"
21	Width of the Bucket	2545 mm	8' 4"
22	Width	2045 mm	80.5"
21	Articulation Angle	+/-	40°

In the interest of continual equipment development, SANY America, Inc. reserves the right to change these specifications at any time without prior notification.

Machine Parameters

Engine	
Engine Model	Deutz TCD6.1
Max Gross Power	184 hp
Net Engine Power	158 hp
Max Gross Torque	634 ft lbs
Displacement	6.1 ltr

Operating	
Bucket Capacity	3.2 cubic yards
Breakout Force	27,143 lbs
Tipping Load Straight	17,460 lbs
Tipping Load @ Full Turn	17,007 lbs
Clearance (full lift 45° dump)	8' 10"
Reach (full lift 45° dump)	3' 3"

	Weight	
L	Operating Weight	32,222 lbs

Hydraulic System	
Max Flow	58 GPM
Max Pressure	3,916 PSI

Hydraulic Cycle Times	
Raise	5.2 sec
Dump	1.3 sec
Float Down	3.0 sec
Total Cycle Time	9.5 sec

Service Capacities		
Fuel Tank	60 gal	
Cooling System	8.7 gal	
Engine Crankcase	4.1 gal	
Transmission	10.6 gal	
Front Axle	9.2 gal	
Rear Axle	9.2 gal	
Hydraulic Tank	34 gal	
DEF Tank	2.6 gal	

Transmission	
Shift Modes	Automatic, Manual, Kick Down
Forward Gear 1-4	7-40 mph
Reverse Gear 1-3	7-26 mph

Power Train	
Front Axle	Fixed
Traction Aid	Manual Differential Lock
Rear Axle	Oscillating
Traction Aid	Open Differential
Service Brakes	Wet Disk
Parking Brake	Disk Brake

SANY America Inc.

318 Cooper Circle • Peachtree City, GA 30269 • T: 470-552-SANY F: 770-632-7820 • **sanyamerica.com**





